



EverExceed® Patented Robust AGM Technology

ST-6230

VALVE REGULATED LEAD ACID BATTERY FOR TELECOM / ELECTRIC UTILITY APPLICATIONS

6V 230 AH @ 10 HR to 1.80VPC

6V 261 AH @ 20 HR to 1.75VPC

LONG DURATION

HIGH PERFORMANCE



Innovative Features



- ◆ Thick positive plate design for maximum service float life 12 years design life @ 20°C(68°F).
- ◆ Valve regulated lead acid battery (VRLA).
- ◆ High-Compression Absorbed Glass Mat technology (AGM) for greater than 99% recombination efficiency.
- ◆ Proprietary Fixed Orifice Plate Pasting technology applying active materials on both sides of the grid for consistent cell-to-cell performance, higher capacity and uniform grid protection.
- ◆ Operates at a low internal pressure.
- ◆ Heavy duty insert copper alloy terminals for ease of assembly, reduced maintenance and increased safety.
- ◆ Advanced lead tin calcium alloy, reduces grid corrosion and promotes long battery life.
- ◆ Over-sized, through the partition inter-cell welds provide low resistance connections, with minimal power loss.
- ◆ Flame arresting, low pressure safety release venting system for individual cells, recognized per U.L. 924.
- ◆ Multicell design for ease of installation and maintenance
- ◆ Horizontal or vertical operation.
- ◆ **Standard:**
Reinforced ABS (UL 94HB) container and cover
- ◆ **Optional:**
Flame-retardant reinforced ABS container and cover compliant with U.L.94 V-0 with an Oxygen limiting Index of greater than 28%.

6 VOLTS - 230 AMPERE HOUR @ 10 HOUR RATE

AH Capacity to 1.80VPC @ 68°F (20°C)





End Point Volts/Cell	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.80	152	166	177	180	196	204	221	230	235	253

For Telecom / Electric Utility Applications



Standard Range VRLA

EverExceed®
power your applications



Length: 323mm Width: 178mm Height: 230mm

Electrical Specifications

Cells Per Unit	Voltage Per Unit	Weight	Electrolyte	Maximum Discharge Current@5s	Short Circuit Current	Internal Resistance (mΩ)
3	6.42	69.3lbs 31.5kg	SG = 1.300	2300 Amps	5600 Amps	2.0

Capacity	261 Ah @ 20 hr. rate to 1.75 volts per cell @ 68°F (20°C). 230 Ah @ 10 hr. rate to 1.80 volts per cell @ 68°F (20°C).
Applicable Operating Temperature Range	-40°F (-40°C) to +158°F (70°C).
Ideal Operating Temperature Range	+68°F (+20°C) to +82.4°F (28°C).
Floating Charging Voltage	6.75 to 6.90 VDC/unit Average at 68°F~77°F (20°C~25°C).
Recommended Maximum Charging Current Limit	57.5 Amperes (0.25C10 Amperes)
Equalization and Cycle Service Charging Voltage	7.05 to 7.20 VDC/unit Average at 68°F~77°F (20°C~25°C).
Maximum AC Ripple (Charger)	0.5% RMS or 1.5% P-P of float charge voltage recommended for best results. Maximum voltage allowed = 1.4% RMS (4% P-P). Maximum current allowed = 1.15 amperes RMS (C/10).
Self Discharge	EverExceed Standard Range batteries may be stored for up to 12 months at 68°F~77°F (20°C~25°C) and then a freshening charge is required. For higher temperatures the time interval will be shorter.
Accessories	Inter unit connectors racks and cabinet systems are available.
Terminal: Inserted	Threaded copper alloy insert terminal
Terminal Hardware Initial Torque: Inserted Terminal	11 N-m

Constant Power Discharging Ratings - Watts Per Cell @ 20°C (68°F)

End Point Volts/Cell	15min	30min	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.85	680	438	276	199	164	111	91.5	76.1	52.5	43.8	37.9	24.9
1.80	694	447	282	213	168	116	95.8	79.8	54.7	45.5	38.9	25.5
1.75	735	464	293	220	174	118	97.7	81.4	55.6	46.4	39.6	26.1

Constant Current Discharging Ratings - Amperes Per Cell @ 20°C (68°F)

End Point Volts/Cell	15min	30min	60min	1.5hr	2hr	3hr	4hr	5hr	8hr	10hr	12hr	20hr
1.85	368	234	149	104	83.0	56.6	46.4	38.5	26.7	22.0	18.7	12.1
1.80	375	239	152	111	88.3	60.3	49.1	40.9	27.7	23.0	19.6	12.7
1.75	407	251	155	113	90.1	61.5	50.4	41.5	28.3	23.7	20.1	13.0

Note: Batteries to be mounted with 0.5 in (1.25 cm) spacing minimum and free air ventilation.
Specifications subject to change without notification.

