





HIGH PERFORMANCE AM 12-0.8

SEALED RECHARGEABLE LEAD ACID BATTERY

Dimensions and Terminal



Length:96mm	Width:25mm	Height :62mm
Total Height :62mm		



AINO MICRO Range VRLA

Innovative Features

- 5~8 years design life @ 20°C(68°F) ambient temperature, 80% remaining capacity;
- UL Recognized component;
- Rechargeable VRLA batteries with an electrolyte retained in a glass mat with a very fine glass fibre structure.
- High-Compression Absorbed Glass Mat technology (AGM) for over 99% recombination efficiency.
- Proprietary Fixed Orifice Plate Pasting technology applying active materials on both sides of the grid for consistent cell-to-cell performance, higher capacity and uniform grid protection.
- Perfect combination between energy storage performance and reliability;
- Operates at a low internal pressure;
- Low self-discharge rate (less than 3% / month @ 20°C(68°F);
- Grid plate construction consisting of a Lead Calcium Tin alloy;
- High impact resistant ABS resin cases and covers;
- Available in V-0 Flame Retardant Material;
- In compliance with IEC 896-2;
- Wide operating temperature range;
- Sealed construction for operation in any position.


Performance Specifications

Normal Voltage	12V	
Normal Capacity	20 hour rate (40.0 mA to 10.5 volts):	0.80 Ah
	10 hour rate (72.0 mA to 10.5 volts):	0.72 Ah
	5 hour rate (130 mA to 10.2 volts):	0.65 Ah
	1 hour rate (480 mA to 9.00 volts):	0.48 Ah
Internal Resistance	150 milliohms	
Approximate Weight	0.35 kg (0.77 lbs)	
Applicable Operating Temperature Range	-40°C(-40°F) to +70°C (+158°F)	
Ideal Operating Temperature Range	+20°C (+68°F) to +28°C (+82.4°F)	
Charge Retention (Shelf Life) at 68°F(20°C)	1 month	97%
	3 month	91%
	6 month	85%
Standby Service	8 years	
Cycle Service	100% depth of discharge	350 cycles
	50% depth of discharge	650 cycles
	30% depth of discharge	1300 cycles
Standard Terminals	Wire Leads & Plug	


AINO MICRO Range VRLA

EverExceed®
power your applications


LIFE CHARACTERISTICS IN CYCLE SERVICE




Float Service Life




TEMPERATURE EFFECTS vs CAPACITY



SHELF LIFE AND STORAGE



OPEN CIRCUIT VOLTAGE vs REMAINING CAPACITY



DISCHARGE CHARACTERISTICS

